

TECHNICAL DATASHEET

Cleanroom Transfers



Cleanroom Transfers



TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

Temperature (°C): 200°C Temperature (°F): 392°F

Time: 35 seconds

Pressure: Medium 42.7 - 56.9 psi / 2.9 - 3.9 bar / 3.0 - 4.0 kg/cm2

Carrier Release: Hot peel

LAUNDERING

Cleanroom transfers permanently dye the applied garment material Follow the recommended care instructions of the chosen garment material Suitable for most industrial wash and finishing techniques, including irradiation Do Not Bleach

HANDLING AND STORAGE

Store in a cool, dark environment Keep away from direct sunlight

Direct contact with sweat or oils can cause stains/blemishes in the transfer. We recommend that gloves be worn when applying in order to preserve the finish of the product.

COMPOSITION

Ink - Dye Sublimation ink Carrier - Paper

HEALTH & SAFETY

This product is identified as Non-Hazardous to the end user No PPE is required during application**

ENVIRONMENTAL / RECYCLING

Paper Carrier - Widely recyclable

^{**}Any furnes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application.