

TECHNICAL DATASHEET

Security Pockets



Security Pockets



TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

Temperature (°C): 210°C Temperature (°F): 410°F

Time: 15 - 20 seconds

Pressure: High 56.9 - 71.1 psi / 3.9 - 4.9 bar / 4.0 - 5.0 kg/cm2

Special Note: Pre-press recommended

LAUNDERING

Suitable for Industrial Laundering up to 85°C Suitable for Industrial Drying Techniques - Medium Suitable for Dry-Cleaning Iron - Medium, On Reverse Do Not Bleach Do Not wash with strong Acid or Alkaline additives

HANDLING AND STORAGE

Store in a cool, dry environment at a stable temperature of ~20°C Store away from direct sunlight

COMPOSITION

Layered Polycotton Fabric construction Ink - Solvent-based (Optional) 100% Polyester Thread Thermoplastic Polyurethane Adhesive Film

HEALTH & SAFETY

This product is identified as Non-Hazardous to the end user No PPE is required during application**

ENVIRONMENTAL / RECYCLING

Non-Recyclable

^{**}Any furnes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application.